

# 0.5 GHz TO 20 GHz ULTRA-BROADBAND CONVERTERS

narda  MITEQ

## DC SERIES MODEL DC-0.5/20G



### FEATURES

- 0.5 GHz to 20 GHz RF input
- 2 Hz tuning resolution
- Very low phase noise
- 1200  $\pm$ 250 MHz L-Band output
- 70  $\pm$ 20 MHz, 140  $\pm$ 40 MHz, and 160  $\pm$ 40 MHz selectable IF output
- Independent 42 dB gain programming in 1 dB step of L-Band and IF outputs
- Independent conversion sense programming of IF and L-Band outputs
- Output IP3 > 25 dBm
- Remote/local programming via full keypad entry
- System parameters programmable via continuous-turn rotary control with self-contained push button selection switch

### OPTIONS

- Built-in self-test and diagnostic features
- Combination of up to eight different bandwidth IF filters centered at 70 MHz, 140 MHz and 160 MHz
- Programmable 30 dB in 10 dB steps front-end attenuator for high-power input signals
- Ethernet programming

The Narda-MITEQ model DC-0.5/20G is a very high-performance, ultra-broadband 2 Hz step agile downconverter. This downconverter accepts RF signals from 0.5 GHz to 20 GHz and provides one selectable IF output of either 70 MHz, 140 MHz or 160 MHz and one L-Band output at 1200 MHz. The frequency conversion sense of both outputs can be independently programmed as inverted or noninverted. Independent gain programming of 42 dB in 1 dB step is provided for both outputs. The superb phase noise makes this system ideal for most applications, including the stringent requirements of high-order QAM. All system parameters are locally programmable by the front panel keypad and rotary knob, or remotely programmable via RS-422/RS-485/RS-232.

# 0.5 GHz TO 20 GHz ULTRA-BROADBAND CONVERTERS

## SPECIFICATIONS

Input characteristics	
Input frequency	0.5 GHz to 20 GHz
Level	to -35 dBm fully compliant
Impedance	50 ohms
Input VSWR	2.5:1 maximum
Noise figure	15 dB maximum at maximum gain
Output characteristics	
IF output (selectable from these IF bands)	
IF center frequency	70 MHz
3 dB bandwidth	±20 MHz minimum
Gain flatness	±0.4 dB typical, ±0.7 dB maximum
IF center frequency	
3 dB bandwidth	±40 MHz minimum
Gain flatness	±0.6 dB typical, ±1.0 dB maximum
IF center frequency	
3 dB bandwidth	±40 MHz minimum
Gain flatness	±0.8 dB typical, ±1.0 dB maximum
L-Band output	
3 dB bandwidth	±250 MHz minimum
Gain flatness	±0.9 dB typical, ±1.4 dB maximum
Impedance	50 ohms
Output VSWR	2:1 maximum
Signal monitor	-20 dBc nominal
Frequency sense	Programmable
Transfer characteristics	
Conversion sense programming	Inverted or noninverted
Fine-tuning step size	2 Hz
Tuning speed	< 100 ms
Gain programming	
L-Band and IF outputs	42 dB
Programming resolution	1 dB
Level stability	< ±0.5 dB/day maximum at constant temperature
Image rejection	60 dB minimum
LO leakage at input	-90 dBm maximum
Group delay variations	3 ns peak-to-peak, typical over 80% of 3 dB bandwidth, 6 ns peak-to-peak, maximum over 80% of 3 dB bandwidth (does not include group delay of the IF switchable filters)
IP3 (output)	25 dBm minimum
Spurious outputs	
Spurious-free dynamic range	60 dB two tones 2 MHz apart at -38 dBm at 30 dB gain
LO spurious rejection	-80 dBm typical
Independent spurs	> 60 dB
Frequency stability	±2 x 10 <sup>-8</sup> , 0 °C to 50 °C fixed temperature after 24 hours power on
Frequency reference	
Reference LO	Internal, external or auto-selectable
External reference input	10 MHz, 0 dBm, ±2 dBm
Internal reference output	10 MHz, 0 dBm, ±2 dBm
Phase noise	Offset from carrier dBc/Hz (typical)
	100 Hz -68 dBc
	1 kHz -90 dBc
	10 kHz -96 dBc
	100 kHz -104 dBc
	1000 kHz -125 dBc

## SPECIFICATIONS (CONTINUED)

Local Control	
DC-0.5/20G .....	Via front-panel keypad, LCD display and continuous-turn rotary control with self-contained push button selection switch
Programmable settings .....	Stored in nonvolatile memory
Rotary Control.....	System parameters programmable via continuous-turn rotary control with self-contained push button selection switch
Local Alarms .....	Power supply status Three LO lock status Fan failure Programmable temperature warning Programmable over temperature trip point
Remote Interface .....	RS-422, RS-485 and RS-232 Ethernet programming (optional)

## OPTIONS

Missing option numbers are not applicable for this product.

- DC1. Up to six switchable IF filters at 70 MHz, 140 MHz or 160 MHz available
  - DC1A. Up to two additional filters
  - DC1B. Up to six additional filters

### Filter Selection Chart

Select the letter code from the following table of available IF filter bandwidth to form part number with this option (see sample part number below)

Code	Bandwidth (MHz)	70 MHz	140 MHz	160 MHz
A	0.25		X	
B	0.50		X	
C	2.5		X	
D	5.0		X	
E	8.0		X	
F	20.0	X		X
G	24.0		X	
H	40.0	STD	X	
J	80.0		STD	STD

STD = Included in standard model; X = Available optional bandwidths for corresponding IF frequencies

- DC2. Programmable front end 30 dB attenuator for high-power input signals (RF input up to -5 dBm)
- DC3. Ethernet programming
  - 10/100 mB 10Base-T interface
  - Web-browser-based configuration
  - SNMP 1.0 configuration
  - Alarm reporting via SNMP Trap
  - Telnet access
  - Password protection
- DC4. DCBIT (Built-in-test): Built-in microwave self-test

## ORDERING INFORMATION

Specify unit by its model number. Example of a full model number:

DC-0.5/20G-DC1B-70F140ABCD160F-DC2-DC4

This means base unit DC-0.5/20G features Option DC1B with IF filter bandwidth F available at 70 MHz and 160 MHz, and IF filter bandwidths A, B, C and D available at 140 MHz (in addition to the IF filter bandwidths included in the base model). The unit also features Options DC2 and DC4.

# 0.5 GHz TO 20 GHz ULTRA-BROADBAND CONVERTERS

## GENERAL SPECIFICATIONS

### PRIMARY POWER REQUIREMENTS

Voltage .....90 VAC to 250 VAC  
Frequency .....47 Hz to 63 Hz

### PHYSICAL

Weight.....33.1 lb. [15 kg] nominal  
Overall dimensions .....19" [482.6 mm] x 3.5" [88.9 mm] (2RU) x 22" [558.8 mm] maximum  
Rear-panel connectors

RF .....SMA female  
L-Band output .....SMA female  
IF.....BNC female  
IF signal monitor .....BNC female  
Remote interface .....DEM-9S for RS-422/RS-485/RS-232  
Summary alarm .....DE-25P  
External reference input .....BNC female  
Reference output.....BNC female  
Ethernet .....RJ-45 (optional)  
Opto interface to DC-20/26.5G and  
DC-20/40G .....10-pin header with ejector

### ENVIRONMENTAL

#### Operating

Temperature .....0 °C to 50 °C  
Full compliance temperature range .....10 °C to 40 °C  
Relative humidity.....Up to 95% at 30 °C, noncondensing  
Atmospheric pressure .....Up to 10,000 feet (40,000 feet optional)

#### Nonoperating

Temperature.....-30 °C to +70 °C  
Relative humidity.....Up to 95% at 40 °C, noncondensing  
Atmospheric pressure .....Up to 40,000 feet  
Shock and vibration .....Rough handling

## TYPICAL REAR-PANEL VIEW



**narda**  **MITEQ**

435 Moreland Road

Hauppauge, NY 11788

Tel: 631-231-1700

Fax: 631-231-1711

Email: [componentsnm@nardamiteq.com](mailto:componentsnm@nardamiteq.com)

[www.nardamiteq.com](http://www.nardamiteq.com)

The material presented in this datasheet was current at the time of publication. Narda-MITEQ's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current.

This material consists of Narda-MITEQ general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.  
D-350D/03.16.17