

PULSE MODULATED AND POWER GATED AMPLIFIERS


AFSW/AFTL SERIES

FEATURES PULSE MODULATED

- Modulation rates up to 500 kHz PRF
- Video leakage approximately 250 mV
- Rise time < 50 ns
- Fall time < 250 ns

POWER GATED

- Power can be turned “on” or “off” by applying a TTL signal
- On/off rates up to 10 kHz
- Rise time < 1.2 μ s
- Fall time < 3.5 μ s




MODEL NUMBER	FREQUENCY RANGE (GHz)	GAIN (dB, Min.)	GAIN FLATNESS (\pm dB, Max.)	NOISE FIGURE (dB, Max.)	VSWR IN/OUT (Max.)	OUTPUT POWER @ 1 dB COMP. (dBm, Min.)	NOM. DC POWER (+15 V, mA)
PULSE MODULATED AMPLIFIERS							
AFSW3-04000800-10	4-8	30	1	1	2:1	10	125
AFSW4-08001200-11	8-12	32	1	1.1	2:1	10	150
AFSW3-02000800-15	2-8	26	1	1.5	2:1	10	125
AFSW3-00100600-16	0.1-6	28	1.2	1.6	2:1	10	125
AFSW3-00100800-20	0.1-8	26	1.2	2	2:1	10	125
AFSW4-00101200-30	0.1-12	26	1.5	3*	2:1	10	150
AFSW5-00101800-35	0.1-18	25	2	3.5*	2.2:1	10	200
POWER GATED AMPLIFIERS							
AFTL3-04000800-09	4-8	30	1	0.9	2:1	10	125
AFTL4-08001200-11	8-12	32	1	1.1	2:1	10	150
AFTL3-02000800-15	2-8	26	1	1.5	2:1	10	125
AFTL3-00100600-16	0.1-6	28	1.25	1.6	2:1	10	125
AFTL3-00100800-20	0.1-8	26	1.25	2	2:1	10	125
AFTL4-00101200-30	0.1-12	26	1.5	3*	2:1	10	150
AFTL5-00101800-35	0.1-18	25	2	3.5*	2.2:1	10	200
AFTL5-00101800-25	0.1-18	25	2.25	2.5*	2:1	10*	200
AFTL4-00102650-40	0.1-26.5	18	2.5	4*	2.5:1	8*	150


* Above 500 MHz.
NOTE: See pages 66 and 68 for outlines.

BLOCK DIAGRAMS

PULSE MODULATED



POWER GATED



100 Davids Drive, Hauppauge, NY 11788
 TEL.: (631) 439-9220 • FAX: (631) 436-7430
 e-mail: components@miteq.com • www.miteq.com